



Packaging

1-liter pouch
3.6-liter gallon
18-liter bucket



Pallets

1-liter pouch - 24 boxes with 24 units = 576 units
3.6-liter gallon - 36 trays with 4 units = 144 units
18-liter bucket - 36 units

Consumption

100 ml for 50 kg of cement

Shelf life

Valid for 12 months from the date on which it was manufactured, as long as the storage regulations are observed.

Store in a covered, dry, ventilated place, away from heat sources, in environments with a temperature not exceeding 30°C and in an upright position.

Description

Liquid additive for mortar that provides workability, the addition of air and plasticity, reducing cracks caused by shrinkage cracks.

Where to apply

- ✓ Mortars and plasters in internal and external areas;
- ✓ Laying mortar;
- ✓ Reframing and beams and pillars;
- ✓ Regularization and mechanical protection for waterproofing;

For other applications consult our technical team **DRYKO**.

Advantages

- ✓ Better workability with mortar;
- ✓ Reduces shrinkage cracks;
- ✓ Due to its ability to incorporate air it improves the application process;
- ✓ Replacement of hydrated lime;
- ✓ Reduces inventory space;
- ✓ Reduces the consumption of water in mortar;

Technical Data

Tests	Specification
Aspect	Dark brown liquid
Density	1.000 to 1.020 g/cm ³
pH	Minimum 9

Product Application

With the product in the original packaging, mix for approximately 2 minutes.

Add the product to the cement-sand mixture in the indicated proportion, then add water to obtain the desired viscosity.

Mix until a homogeneous, lump-free paste is formed.

Cleaning

Tools and equipment can be cleaned with water while the product is wet and, after it dries, it must be removed mechanically.



Notes

The mortar trace must be dosed according to the amount of cement. Use specific meter for proper addition of products.

Handling and safety

- ✓ Handle with care.
- ✓ We recommend observing the safety standards established by the competent bodies and the use of appropriate PPE.
- ✓ In case of accidental ingestion, do not force vomiting. In contact with eyes, rinse well with water for at least 15 minutes. In contact with the skin, wash well with soap and water and use a moisturizing cream. See a doctor.
- ✓ Keep out of reach of children and animals.
- ✓ In closed places, if necessary, create forced ventilation.
- ✓ For further information on handling and safety, refer to the product MSDS, available on our website – www.dryko.com.br.
- ✓ Dispose of content/container at an approved waste treatment plant.

the Consumer Protection Code, pointing out that the final performance of the product is directly influenced by the quality of the application and its conditions, including factors such as climate, temperature, storage, and ways of application.

DRYKO may make changes to the products whenever it deems necessary, without prior notice.

The information on this product datasheet is based on our experience and knowledge, for guidance purposes, and in accordance with the procedures of the current standard, with laboratory analyses carried out in accordance with the requirements of the products, uses not provided for in this document will not be considered.

LEGAL NOTICE

DRYKO IMPERMEABILIZANTES guarantees the quality of its products against manufacturing defects, according to the legal provisions of

www.DRYKO.com.br

DRYKO has it covered!

Rua Antônio Rodrigues Filho, 404 | Vila Aeroporto.
Guarulhos | SP | Zip Code (CEP) 07170-325
Phone: 11 2088-5700

