

DRYKOLAJE TOP

Liquid waterproofing blanket



Packaging

4kg gallon
12kg bucket
18kg bucket



Pallets

4 kg – 36 trays with 4 units = 144 units
12 kg – 42 units
18 kg – 36 Units

Finishing

White

Consumption

1.0 to 1.2 kg/m²

Shelf life

Valid for 24 months from the date on which it was manufactured, as long as the storage regulations are observed.

Store in a covered, dry, ventilated place, away from heat sources, in environments with a temperature not exceeding 30°C and in an upright position.

Description

Liquid waterproofing acrylic resin-based blanket resistant to UV rays, ozone and direct rain with excellent finishing coverage.

Where to apply

- ✓ Covering slabs without the moment of people;
- ✓ Reflective paints on fiber cement tiles;
- ✓ UV protection over the asphalt painting system;

For other applications consult our technical team **DRYKO**.

Advantages

- ✓ Ready to use;
- ✓ Application as paint;
- ✓ Non-toxic product;
- ✓ Durable;
- ✓ Can be pigmented;

Technical Data

Tests	Unit	Specification
Specific Mass	g/cm ³	1.300 to 1.400
Solids content	%	48 to 53
Krebs Stormer Viscosity	Ku	120 to 140
Drying between coats	Hours	2 to 3
pH		Minimum 8

Surface preparation

The substrate for applying **DRYKOLAJE TOP** must be clean, free of foreign bodies, mold remains, hardware tips, residues of release or impregnating agents, flaws and niches. On smooth concrete, sand with a steel brush or mechanically to increase porosity and remove release or curing agents.

Level with a minimum slope of 2% towards the water flow points, prepared with cement mortar and medium 1:4 ratio of sand, adding **DRYKOFIX** adhesive in the mortar massing water for better adhesion to the substrate. The mortar must have a flattened finishing, with a minimum thickness of 2 cm.

Emerging pipes and drains must be rigidly fixed. Round off sharp corners and edges. Cracks and fissures must be treated before waterproofing.

www.DRYKO.com.br

DRYKO has it covered!

Rua Antônio Rodrigues Filho, 404 | Vila Aeroporto.
Guarulhos | SP | CEP 07170-325
Phone: 11 2088-5700



DRYKOLAJE TOP

Liquid waterproofing blanket

**Notes**

The mortar used for leveling must not contain lime and water-repellent additives. Wait for the mortar to cure for at least 7 days.

We do not recommend applying the product in rainy weather and with wet substrate. We recommend applying the product at temperatures between 10 and 40°C, and humidity below 85%.

Water-tightness test

Wait for the product to cure after the last coat is applied to conduct the water-tightness test with a minimum duration of 72 hours.

Handling and safety

- ✓ Handle with care.
- ✓ We recommend observing the safety standards established by the competent bodies and the use of appropriate PPE.
- ✓ In case of accidental ingestion, do not force vomiting. In contact with eyes, rinse well with water for at least 15 minutes. In contact with the skin, wash well with soap and water and use a moisturizing cream. See a doctor.
- ✓ Keep out of reach of children and animals.
- ✓ In closed places, if necessary, create forced ventilation.
- ✓ For further information on handling and safety, refer to the product MSDS, available on our website – www.dryko.com.br.
- ✓ Dispose of content/container at an approved waste treatment plant.

Application of DRYKOLAJE TOP

With the product in the original packaging, mix for approximately

2 minutes. Use a roller, a spalter or a brush to apply the product.

While the substrate is dry, apply the 1st coat of **DRYKOLAJE TOP** diluted in 40% water and wait for 2 to 3 hours for it to dry.

Apply the 2nd coat of pure **DRYKOLAJE TOP** in an even layer without excess, respecting the interval between coats of 2 to 3 hours.

Reinforce the entire area of application of the liquid blanket with **DRYKOTELA** and apply subsequent coats until reaching the recommended usage. Make sure that the entire area with **DRYKOTELA** is covered with the product, if there are voids and openings, reapply the product accordingly.

DRYKOLAJE TOP must be left exposed and cannot receive mechanical protection or coating. Do not use on pools and reservoirs.

Cleaning

Tools and equipment can be cleaned with water before drying the product and, after it is dry, the removal must be done mechanically.

LEGAL NOTICE

DRYKO IMPERMEABILIZANTES guarantees the quality of its products against manufacturing defects, according to the legal provisions of the Consumer Protection Code, pointing out that the final performance of the product is directly influenced by the quality of the application and its conditions, including factors such as climate, temperature, storage, and ways of application.

DRYKO may make changes to the products whenever it deems necessary, without prior notice.

The information on this product datasheet is based on our experience and knowledge, for guidance purposes, and in accordance with the procedures of the current standard, with laboratory analyses carried out in accordance with the requirements of the products, uses not provided for in this document will not be considered.

www.DRYKO.com.br

DRYKO has it covered!

Rua Antônio Rodrigues Filho, 404 | Vila Aeroporto.
Guarulhos | SP | CEP 07170-325
Phone: 11 2088-5700

